



The new iGen2750PRO offers a unique upgrade in the 2.75 kVA generator class by having an RCD electrical safety switch approved for workplace use. It delivers clean, reliable power to operate a wide range of electrical devices while remaining lightweight and compact for easy portability. Combining quiet operation, dependable performance and enhanced safety protection, the iGen2750PRO is well suited to both recreational use and jobsite applications.

Features and Benefits

Powerful

High output to operate more electrical devices.

Lightweight

Easy to carry 20 kg with ergonomic handle.

Long Running

Up to 10.1 hours at 1/4 load with a 4.7 litre fuel tank.

Mains Quality Electricity

Safe to power sensitive electronic equipment.

Plug and Play

No assembly required, just add petrol.

Electrical Safety Protection

RCD safety switch approved for workplace use.

Super Quiet

Low noise level ideal for camping or jobsite use.

LED Lights

Illuminate control panel for night-time operation.

Easy to Maintain

Engine oil and air filter servicing without tools.

Warranty Protection

2-year domestic use (conditions apply).



iGen2750PRO Inverter Generator

2200	2750
Running Watts	Starting Watts



Control Panel Functions

Output Voltage (Volts)	Output Frequency (Hz)	Cumulative Run Time (hours)	Current Run Time (hh:mm)
U240	F50.0	0088	01:68



Overload Alarm
Output Indicator
Data Center
Generator Reset Button
LED Panel Lights
240-Volt AC 15-Amp Outlet



Low Oil Alarm
Panel Lights Switch
RCD Safety Switch
LED Panel Lights
Frame Terminal
ECO Throttle Switch

Powering People Since 1886.

Specifications

iGen2750PRO Inverter Generator

ENGINE		240 VOLT AC ELECTRICAL	
Type	1-Cylinder, 4-Stroke, Overhead Valve, Air Cooled	Voltage (V)	240
Displacement (cc)	98	Frequency (Hz)	50
Maximum Speed (rpm)	5,000	Number of Phases	1
Oil Capacity (mL)	350	Continuous Running Power (W) *	2,200
Oil Viscosity	SAE 10W-30	Maximum Starting Power (W)	2,750
Low Oil Shutdown	Yes	Continuous Running Current (A)	9.2
Low Oil Alarm Indicator	Yes	Voltage & Waveform Control	Digital Inverter, Pure Sine Wave Output
Spark Plug	Torch A7RTC	Total Harmonic Distortion (THD)	< 2.5%
Fuel	Unleaded Petrol # (91, 95 or 98 RON)	Receptacles	1 x 15 A, IP66
Fuel Tank Capacity (L)	4.7	Overload Protection	Electronic
Fuel Gauge	No	Overload Indicator	Yes
Fuel Shutoff Valve	Yes	Overload Reset	Push Button
Starting Method	Recoil	RCD Safety Switch	Yes
Run Time @ 1/4 / Full Load	10.1 / 3.2 hours	Alternator	Brushless, Permanent Magnet
Noise Level @ 1/4 / Full Load	54 / 64 dB(A) @ 7 m	Output Ready Indicator	Yes
DIMENSIONS & WEIGHTS		Data Center Display	Output Voltage & Frequency, Current & Cumulative Run Times
Generator L x W x H (mm)	500 x 297 x 456	Control Panel Lights	LED, Operable While Running
Generator Weight - Dry / Wet (kg)	20 / 24	PRODUCT CODES	
Packed L x W x H (mm)	540 x 350 x 521	Product Code	WP iGen2750PRO
Packed Weight (kg)	22	GTIN Barcode	9347923003130

Ethanol blends such as E10 are not recommended.

* Rated output at 1.0 power factor.



Included Accessories