



# Westinghouse

## WPX3800-PRO Pressure Washer

|                 |                   |                       |
|-----------------|-------------------|-----------------------|
| <b>3800 PSI</b> | <b>13.6 L/MIN</b> | <b>3570 BAR.L/MIN</b> |
| Pressure        | Flow Rate         | Cleaning Energy       |

The new Westinghouse WPX3800-PRO pressure washer is equipped with a powerful petrol engine, robust Triplex brass head pump and durable steel wire reinforced pressure hose to deliver sustained high cleaning energy for demanding worksite applications. It offers you a combination of commercial-grade cleaning performance and functional portability in a great value-for-money package.

### Features and Benefits

#### Reliable Performance

High output, 274 cc fuel efficient, 4-stroke Westinghouse OHV petrol engine.

#### Premium Features

Triplex brass head pressure pump, 5 spray nozzles and built-in 3 litre detergent tank.

#### Simple Operation

Colour-coded touch points and quick-connect spray nozzles and hose for ease of use.

#### Ergonomic

Endura-Grasp™ spray gun with 53 cm lance and 15.2 m steel wire reinforced pressure hose.

#### Portable

Sure-grip handles and pneumatic run-flat all-terrain tyres on steel rims.

#### Safety Protection

Spray gun handle with trigger safety lock. Low engine oil level shutdown system.

#### Plug & Play

Just add petrol, detergent and connect to water supply. All other requisites included.

#### Buy With Confidence

2-year domestic or 1-year commercial use warranty coverage (conditions apply).

### 5 Quick-Change Spray Nozzles

| RED              | YELLOW          | GREEN             | WHITE           | BLACK                  |
|------------------|-----------------|-------------------|-----------------|------------------------|
| Intense Cleaning | Strong Cleaning | Moderate Cleaning | Gentle Cleaning | Low Pressure Detergent |
| 0°               | 15°             | 25°               | 40°             | 60°                    |



Powering People Since 1886.

## Specifications

# WPX3800-PRO Pressure Washer

| ENGINE                          |                                                                        |
|---------------------------------|------------------------------------------------------------------------|
| Type                            | 1-Cylinder, 4-Stroke, Overhead Valve, Air Cooled                       |
| Cast Iron Sleeve                | Yes                                                                    |
| Displacement (cc)               | 274                                                                    |
| Speed (rpm)                     | 3,600                                                                  |
| Oil Capacity (mL)               | 700                                                                    |
| Oil Grade                       | SAE 10W-30                                                             |
| Low Oil Shutdown                | Yes                                                                    |
| Spark Plug                      | Torch F7RTC                                                            |
| Fuel                            | Unleaded Petrol (91, 95 or 98 RON) #                                   |
| Fuel Tank Capacity (L)          | 5                                                                      |
| Starting Method                 | Recoil                                                                 |
| Spark Arrestor                  | Yes                                                                    |
| Exhaust Emissions Certification | US EPA and Australia                                                   |
| WATER PUMP                      |                                                                        |
| Pump Type                       | Triplex with Crankshaft, Direct-Drive                                  |
| Pump Construction               | Ceramic Coated Stainless Steel Pistons<br>Forged Brass Alloy Pump Head |
| Maximum Pressure (bar / psi)    | 262 / 3,800                                                            |
| Maximum Flow Rate (L/min)       | 13.63                                                                  |
| Cleaning Energy (bar.L/min)     | 3,570 *                                                                |
| Detergent Injection             | 1:20 (Detergent to Water)                                              |
| Inlet Connector                 | 12 & 18 mm Snap-On Garden Hose Plugs $\Delta$                          |
| Outlet Connector                | PWMA 3/8" Quick Connect Coupler Socket                                 |

| SPRAY GUN AND LANCE                 |                                                           |
|-------------------------------------|-----------------------------------------------------------|
| Spray Gun                           | Trigger Control with Safety Lock                          |
| Lance                               | 533 mm Long, Stainless Steel                              |
| SPRAY NOZZLES                       |                                                           |
| Spray Pattern                       | 0°, 15°, 25° & 40° Wash<br>60° Detergent                  |
| Inlet Connector                     | PWMA 1/4" Quick Connect Coupler Plug                      |
| HIGH PRESSURE HOSE                  |                                                           |
| Pressure Rating (bar / psi)         | 262 / 3,800                                               |
| Length (m / ft)                     | 15.24 / 50                                                |
| Material                            | Steel Wire Reinforced Rubber                              |
| Connectors                          | PWMA 3/8" Quick Connect Plug and Socket Couplers          |
| DETERGENT TANK                      |                                                           |
| Capacity (L)                        | 3                                                         |
| FRAME AND WHEELS                    |                                                           |
| Frame Construction                  | 32 mm Steel Tube                                          |
| Wheels                              | 250 mm Pneumatic Run-Flat All-Terrain Tyres on Steel Rims |
| DIMENSIONS, WEIGHTS & PRODUCT CODES |                                                           |
| Washer L x W x H (mm)               | 990 x 610 x 700                                           |
| Washer Weight - Dry / Wet (kg)      | 41 / 46                                                   |
| Packed L x W x H (mm)               | 605 x 510 x 620                                           |
| Packed Weight (kg)                  | 46                                                        |
| Product Code                        | WP WPX3800-PRO                                            |
| GTIN Barcode                        | 9347923002416                                             |

# Ethanol blends such as E10 are not recommended. \* Class A water jetting system per Australian Standard 4233.1:2013.  $\Delta$  18 mm water supply hose recommended.



# Westinghouse

westinghouseoutdoorpower.com.au

Specifications are subject to change without notice. 2025-08-19