

WPX3800-PRO Pressure Washer



The new Westinghouse WPX3800-PRO pressure washer is equipped with a powerful petrol engine, robust Triplex brass head pump and durable steel wire reinforced pressure hose to deliver sustained high cleaning energy for demanding worksite applications. It offers you a combination of commercial-grade cleaning performance and functional portability in a great value-for-money package.

Features and Benefits

Reliable Performance

High output, 274 cc fuel efficient, 4-stroke Westinghouse OHV petrol engine.

Premium Features

Triplex brass head pressure pump, 5 spray nozzles and built-in 3 litre detergent tank.

Simple Operation

Colour-coded touch points and quick-connect spray nozzles and hose for ease of use.

Ergonomic

Endura-Grasp™ spray gun with 53 cm lance and 15.2 m steel wire reinforced pressure hose.

Portable

Sure-grip handles and pneumatic run-flat all-terrain tyres on steel rims.

Safety Protection

Spray gun handle with trigger safety lock. Low engine oil level shutdown system.

Plug & Play

Just add petrol, detergent and connect to water supply. All other requisites included.

Buy With Confidence

2-year domestic or 1-year commercial use warranty coverage (conditions apply).

5 Quick-Change Spray Nozzles



Specifications

WPX3800-PRO Pressure Washer

ENGINE		
Туре	1-Cylinder, 4-Stroke, Overhead Valve, Air Cooled	
Cast Iron Sleeve	Yes	
Displacement (cc)	274	
Speed (rpm)	3,600	
Oil Capacity (mL)	700	
Oil Grade	SAE 10W-30	
Low Oil Shutdown	Yes	
Spark Plug	Torch F7RTC	
Fuel	Unleaded Petrol (91, 95 or 98 RON) #	
Fuel Tank Capacity (L)	5	
Starting Method	Recoil	
Spark Arrestor	Yes	
Exhaust Emissions Certification	US EPA and Australia	
WATER PUMP		
Pump Type	Triplex with Crankshaft, Direct-Drive	
Pump Construction	Ceramic Coated Stainless Steel Pistons Forged Brass Alloy Pump Head	
Maximum Pressure (bar / psi)	262 / 3,800	
Maximum Flow Rate (L/min)	13.63	
Cleaning Energy (bar.L/min)	3,570 *	
Detergent Injection	1:20 (Detergent to Water)	
Inlet Connector	12 & 18 mm Snap-On Garden Hose Plugs △	
Outlet Connector	PWMA 3/8" Quick Connect Coupler Socket	

SPRAY GUN AND LANCE		
Spray Gun	Trigger Control with Safety Lock	
Lance	533 mm Long, Stainless Steel	
SPRAY NOZZLES		
Spray Pattern	0°, 15°, 25° & 40° Wash 60° Detergent	
Inlet Connector	PWMA ¼" Quick Connect Coupler Plug	
HIGH PRESSURE HOSE		
Pressure Rating (bar / psi)	262 / 3,800	
Length (m / ft)	15.24 / 50	
Material	Steel Wire Reinforced Rubber	
Connectors	PWMA 3/8" Quick Connect Plug and Socket Couplers	
DETERGENT TANK		
Capacity (L)	3	
FRAME AND WHEELS		
Frame Construction	32 mm Steel Tube	
Wheels	250 mm Pneumatic Run-Flat All-Terrain Tyres on Steel Rims	
DIMENSIONS, WEIGHTS & PRODUCT CODES		
Washer L \times W \times H (mm)	990 × 610 × 700	
Washer Weight - Dry / Wet (kg)	41 / 46	
Packed L × W × H (mm)	605 × 510 × 620	
Packed Weight (kg)	46	
Product Code	WP WPX3800-PRO	
GTIN Barcode	9347923002416	

[#] Ethanol blends such as E10 are not recommended. * Class A water jetting system per Australian Standard 4233.1:2013. $^{\triangle}$ 18 mm water supply hose recommended.







