



Westinghouse

WPX4400-PRO Pressure Washer

4400 PSI	15.9 L/MIN	4820 BAR.L/MIN
Pressure	Flow Rate	Cleaning Energy

The new WPX4400-PRO delivers the highest cleaning energy of any pressure washer in the Westinghouse commercial-grade range. The powerful 420 cc petrol engine, heavy-duty Triplex brass head pump and durable steel wire reinforced pressure hose can tackle the biggest worksite cleaning jobs in the shortest amount of time to save your business both money and water.

Features and Benefits

Reliable Performance

High output, 420 cc fuel efficient, 4-stroke Westinghouse OHV petrol engine.

Premium Features

Triplex brass head pressure pump, 5 spray nozzles and built-in 3 litre detergent tank.

Simple Operation

Colour-coded touch points and quick-connect spray nozzles and hose for ease of use.

Ergonomic

Endura-Grasp™ spray gun with 79 cm lance and 15.2 m steel wire reinforced pressure hose.

Portable

Sure-grip handles and pneumatic run-flat all-terrain tyres on steel rims.

Safety Protection

Spray gun handle with trigger safety lock. Low engine oil level shutdown system.

Plug & Play

Just add petrol, detergent and connect to water supply. All other requisites included.

Buy With Confidence

2-year domestic or 1-year commercial use warranty coverage (conditions apply).

5 Quick-Change Spray Nozzles

RED	YELLOW	GREEN	WHITE	BLACK
Intense Cleaning	Strong Cleaning	Moderate Cleaning	Gentle Cleaning	Low Pressure Detergent
0°	15°	25°	40°	60°



Powering People Since 1886.

Specifications

WPX4400-PRO Pressure Washer

ENGINE	
Type	1-Cylinder, 4-Stroke, Overhead Valve, Air Cooled
Cast Iron Sleeve	Yes
Displacement (cc)	420
Speed (rpm)	3,600
Oil Capacity (mL)	1,100
Oil Grade	SAE 10W-30
Low Oil Shutdown	Yes
Spark Plug	Torch F7RTC
Fuel	Unleaded Petrol (91, 95 or 98 RON) #
Fuel Tank Capacity (L)	6.5
Starting Method	Recoil
Spark Arrestor	Yes
Exhaust Emissions Certification	US EPA and Australia
WATER PUMP	
Pump Type	Triplex with Crankshaft, Direct-Drive
Pump Construction	Ceramic Coated Stainless Steel Pistons Forged Brass Alloy Pump Head
Maximum Pressure (bar / psi)	303 / 4,400
Maximum Flow Rate (L/min)	15.9
Cleaning Energy (bar.L/min)	4,820 *
Detergent Injection	1:20 (Detergent to Water)
Inlet Connector	12 & 18 mm Snap-On Garden Hose Plugs Δ
Outlet Connector	PWMA 3/8" Quick Connect Coupler Socket

SPRAY GUN AND LANCE	
Spray Gun	Trigger Control with Safety Lock
Lance	787 mm Long, Stainless Steel
SPRAY NOZZLES	
Spray Pattern	0°, 15°, 25° & 40° Wash 60° Detergent
Inlet Connector	PWMA 1/4" Quick Connect Coupler Plug
HIGH PRESSURE HOSE	
Pressure Rating (bar / psi)	310 / 4,500
Length (m / ft)	15.24 / 50
Material	Steel Wire Reinforced Thermoplastic Polyurethane
Connectors	PWMA 3/8" Quick Connect Plug and Socket Couplers
DETERGENT TANK	
Capacity (L)	3
FRAME AND WHEELS	
Frame Construction	32 mm Steel Tube
Wheels	300 mm Pneumatic Run-Flat All-Terrain Tyres on Steel Rims
DIMENSIONS, WEIGHTS & PRODUCT CODES	
Washer L x W x H (mm)	985 x 610 x 760
Washer Weight - Dry / Wet (kg)	60 / 69
Packed L x W x H (mm)	695 x 655 x 715
Packed Weight (kg)	68
Product Code	WP WPX4400-PRO
GTIN Barcode	9347923002423

Ethanol blends such as E10 are not recommended. * Class A water jetting system per Australian Standard 4233.1:2013. Δ 18 mm water supply hose recommended.

