



The new iGen2250 offers you an appealing fresh choice in the most popular 2 kVA generator class. It efficiently and quietly delivers ample clean power capable of running a wide range of electrical devices while still being light and compact enough for single-handed portability. The unique combination of enhanced affordability, superior performance and high-end features puts the iGen2250 at the forefront of the Westinghouse inverter generator line-up.

iGen2250 Inverter Generator

1800 | **2250**
Running Watts | Starting Watts

Features and Benefits

Powerful

High output to operate more electrical devices.

Super Quiet

Low dB noise level ideal for tranquil camping use.

Long Running

Up to 11.3 hours @ 1/4 load on a single tank of fuel.

Mains Quality Electricity

Safe to power all your electronic equipment.

Plug and Play

No assembly required before use, just add petrol.

Lightweight

Easy to carry 19 kg with its ergonomic handle.

Clean and Efficient

80 cc, 4-stroke OHV petrol engine with ECO throttle.

LED Lights

Illuminate control panel for operating at night-time.

Easy to Maintain

Engine oil and air filter servicing without tools.

Warranty Protection

2-year domestic use (conditions apply).



Control Panel Functions

Output Voltage (Volts) Output Frequency (Hz) Cumulative Run Time (hours) Current Run Time (hh:mm)

U240 F50.0 0088 0 1:68



Powering People Since 1886.

iGen2250

Inverter Generator

Specifications

ENGINE		240 VOLT AC ELECTRICAL	
Type	1-Cylinder, 4-Stroke, Overhead Valve, Air Cooled	Voltage (V)	240
Displacement (cc)	80	Frequency (Hz)	50
Maximum Speed (rpm)	5,000	Number of Phases	1
Oil Capacity (mL)	350	Continuous Running Power (W) *	1,800
Oil Viscosity	SAE 10W-30	Maximum Starting Power (W)	2,250
Low Oil Shutdown	Yes	Continuous Running Current (A)	7.5
Low Oil Alarm Indicator	Yes	Voltage & Waveform Control	Digital Inverter, Pure Sine Wave Output
Spark Plug	Torch E6RTC	Total Harmonic Distortion (THD)	< 2.5%
Fuel	Unleaded Petrol # (91, 95 or 98 RON)	Receptacles	2 x 15 A, IP44
Fuel Tank Capacity (L)	4.7	Overload Protection	Electronic
Fuel Gauge	No	Overload Indicator	Yes
Fuel Shutoff Valve	Yes	Overload Reset	Push Button
Starting Method	Recoil	Alternator	Brushless, Permanent Magnet
Run Time @ 1/4 / Full Load	11.3 / 3.8 hours	Output Ready Indicator	Yes
Noise Level @ 1/4 / Full Load	53 / 62 dB(A) @ 7 m	Data Center Display	Output Voltage & Frequency, Current & Cumulative Run Times
DIMENSIONS, WEIGHTS & PRODUCT CODES		Control Panel Lights	LED, Operable While Running
Generator L x W x H (mm)	485 x 297 x 456	12 VOLT DC ELECTRICAL	
Generator Weight - Dry / Wet (kg)	19 / 23	Voltage (V)	12
Packed L x W x H (mm)	540 x 350 x 521	Maximum Current (A)	8
Packed Weight (kg)	22	Maximum Power (W)	100
Product Code	WP iGen2250	Receptacle	8 A, IP44
GTIN Barcode	9347923002355	* Rated output at 1.0 power factor. # Ethanol blends such as E10 are not recommended.	

