Westinghouse

The new iGen3750PRO sets a new standard in the 3 kVA inverter generator class by combining high power output with advanced safety and user-focused features. It offers the convenience of electric start and remote-control operation, together with an integrated RCD safety switch approved for workplace use. Designed for portability, reliability and ease of operation, the iGen3750PRO is ideal for demanding jobsite and professional applications.

iGen3750PRO
Inverter Generator

3000	3750
Running Watts	Starting Watts

PURE SINE WAVE

Features and Benefits

Powerful
Highest starting and running power outputs in its class.

Remote Control
Convenient push-button start and stop from a distance.

LED Lights
Illuminate control panel for night-time operation.

Lightweight
Portable at just 27 kg with handles and wheels.

Long Running
Up to 8.8 hours at 1/4 load with a 6.3 litre fuel tank.

Plug and Play
No assembly required, just add petrol.

Electric Start
One touch power-up by Lithium-Ion battery.

Electrical Safety Protection
RCD safety switch approved for workplace use.

Battery Charger
Keep your generator ready to go at all times.

Super Quiet
Low noise level ideal for jobsite or off-grid RV use.

Mains Quality Electricity
Safe to power sensitive electronic equipment.

Warranty Protection
2-year domestic use (conditions apply).

ELECTRIC START | RCD Safety Switch | Remote Control | LED Panel Lights | Battery Charger

Control Panel Functions

Powering People Since 1886.

iGen3750PRO
Inverter Generator

Specifications

ENGINE	
Type	1-Cylinder, 4-Stroke, Overhead Valve, Air Cooled
Displacement (cc)	141
Maximum Speed (rpm)	4,800
Oil Capacity (mL)	400
Oil Viscosity	SAE 10W-30
Low Oil Shutdown	Yes
Low Oil Alarm Indicator	Yes
Spark Plug	Torch A7RTC
Fuel	Unleaded Petrol # (91, 95 or 98 RON)
Fuel Tank Capacity (L)	6.3
Fuel Shutoff Valve	Yes, Independent
Starting Method	Local / Remote Electric and Recoil
Battery	12 V, Lithium-Ion
Run Time @ 1/4 / Full Load	8.8 / 3.0 hours
Noise Level @ 1/4 / Full Load	57 / 63 dB(A) @ 7 m
DIMENSIONS & WEIGHTS	
Generator L × W × H (mm)	565 x 320 x 490
Generator Weight - Dry / Wet (kg)	27 / 32.5
Packed L × W × H (mm)	657 x 400 x 506
Packed Weight (kg)	31

240 VOLT AC ELECTRICAL	
Voltage (V)	240
Frequency (Hz)	50
Number of Phases	1
Continuous Running Power (W) *	3,000
Maximum Starting Power (W)	3,750
Continuous Running Current (A)	12.5
Voltage & Waveform Control	Digital Inverter, Pure Sine Wave Output
Total Harmonic Distortion (THD)	< 2.5%
Receptacles	1 x 15 A, IP66
Overload Protection	Electronic
Overload Indicator	Yes
Overload Reset	Push Button
RCD Safety Switch	Yes
Alternator	Brushless, Permanent Magnet
Output Ready Indicator	Yes
Data Center Display	Output Voltage & Frequency, Current & Cumulative Run Times
Control Panel Lights	LED, Operable At All Times
PRODUCT CODES	
Product Code	WP iGen3750PRO
GTIN Barcode	9347923003147

Ethanol blends such as E10 are not recommended.

* Rated output at 1.0 power factor.

Plug-In Battery Charger

Extendable Handle

Included Accessories

Westinghouse

westinghouseoutdoorpower.com.au

Specifications are subject to change without notice. 2026-03-25